





Technical Specifications

| ENGINE SPECIFICATIONS | ALTERNATOR SPECIFICATIONS |
|---|--|
| Manufacturer | Manufacturer |
| Model | Model |
| Emissions Compliance | Туре |
| Number of Cylinders | Excitation System |
| Displacement, L (cu. in.) | Voltage Regulator Type |
| Aspiration | Number of Leads |
| Power at Rated RPM, kW (HP) | Insulation Class |
| Aftertreatment System | Temp Rise |
| Oil Pan Capacity, L (gal.)inc. filters | Bearing: Quantity, Type |
| Oil Filter: Quantity, type | Voltage Regulation (steady state) |
| Air Cleaner Type | One-Step Load Acceptance |
| Governor Type | Peak Motor Starting kVA, 30% Voltage Dip |
| ENGINE ELECTRICAL SYSTEM | CONTROLS & CONNECTIONS |
| SPECIFICATIONS | SPECIFICATIONS |
| Battery Voltage | Generator Control Panel |
| Battery Size | Voltage Adjustment |
| Ground Polarity | Main Circuit Breaker |
| Starter Motor Voltage | Security Cover |
| Battery Charging Alternator | Emergency Stop |
| FUEL SYSTEM SPECIFICATIONS | Load Connections |
| Fuel System Type | Remote Start/Stop Compatability |
| Fuel Requirement | Shore Power Connection |
| Fuel Filter: Quantity, type | Convenience Receptacles |
| Fuel Tank Capacity L (gal.) | OPTIONAL TRAILER SPECIFICATIONS |
| DEF Tank Capacity, L (gal.) | Compliance |
| COOLING SYSTEM SPECIFICATIONS | Number of Axles |
| Cooling System Type | GVWR |
| Cooling Fan Type | Brakes |
| Cooling System Capacity, L (gal.) | Hitch Type, Size |
| Ambient Temperature Capability, deg C (F) | Trailer Electrical Connection |
| ENCLOSURE SPECIFICATIONS | Hitch/Stabilizing Jacks |
| Material | Safety Chains |
| Exterior Finish | Tire Size |
| SOUND DATA | Wheels |
| dB(A) @ 7m (23ft), Prime Rating | Spare Tire |

Generator Output Options

| VOLTAGE RATING (VAC) | FREQ. | PRIME kW | PRIME AMP | STANDBY kW | STANDBY AMP | LEAD CONFIG | MAIN BREAKER AMP | LOCKED ROTOR kVA (at 30% Voltage dip) |
|-------------------------|-------|-------------|-----------|---------------|----------------|-------------|---------------------|--|
| 277/480V 3-Phase | 60 Hz | | | | | High Wye | | |
| 120/208V 3-Phase | 60 Hz | | | | | Low Wye | | |
| 120/240V 3-Phase | 60 Hz | | | | | Delta | | |
| 120/240V 1-Phase | 60 Hz | | | | | Zig Zag | | |

Weights & Dimensions

| OVERALL DIMENSIONS: in (m) | | WEIGHT | CONFIGURATION | GVWR | |
|----------------------------|-------|--------|---------------------|------------------------|---------|
| LENGTH | WIDTH | HEIGHT | (w/o fuel): lb (kg) | CONTROLATION | lb (kg) |
| | | | | TOWABLE | |
| | | | | ENCLOSED - SKID + TANK | N/A |
| | | | | ENCLOSED - SKID ONLY | N/A |
| | | | | OPEN - SKID + TANK | N/A |
| | | | | OPEN - SKID ONLY | N/A |

Fuel & DEF Consumption

| | | DIESEL FUEL | | DIES | RUN TIME | | |
|--------|----------------------|--------------------|----------------------|----------------------|--------------------|----------------------|---------------|
| % LOAD | TANK SIZE gal (I) | PRIME gph (lph) | STANDBY gph (lph) | TANK SIZE gal (I) | PRIME gph (lph) | STANDBY gph (lph) | PRIME (hours) |
| *25% | | | | | | | |
| *50% | | | | | | | |
| 75% | | | | | | | |
| 100% | | | | | | | |

* Operation at light loads for extended periods of time is not recommended, and can negatively impact performance, reliability, and/or durability of the engine & generator system.